

Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product, and must be read in conjunction with the Safety Data Sheet (SDS) attached.

Product Name: ESPE™ Imprint™ 4 Super Quick Light Refill

Manufacturer: 3M

SDS Expiry: 10 December 2023

Supplier Details: Henry Schein New Zealand
23 William Pickering Drive, Albany
PO Box 101 140, North Shore, Auckland 0745
Ph. 0800 808 855
www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre – 0800POISON/0800764766 (24 Hours)
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 6

HSNO Group Standard: Dental Products Subsidiary Hazard Group Standard HSR002558

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared on 17 October 2019

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



Safety Data Sheet

© 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	31-6662-6	Version number:	2.00
Issue Date:	10/12/2018	Supersedes date:	21/04/2013

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

IDENTIFICATION:

1.1. Product identifier

3M™ ESPE™ Imprint™ 4 Super Quick Light Refill

Product Identification Numbers

70-2011-4145-7

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

31-4864-0, 31-4875-6

One or more components of this KIT is classified as a hazardous substance in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017.

TRANSPORT INFORMATION

NOT HAZARDOUS FOR TRANSPORT

Revision information:

Complete document review.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>



Safety Data Sheet

© 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 31-4864-0 **Version number:** 2.00
Issue Date: 10/12/2018 **Supersedes date:** 21/04/2013

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Skin Sensitiser: Category 1	6.5B Skin sensitiser

2.2. Label elements

SIGNAL WORD

WARNING!

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

Symbols:

Exclamation mark |

Pictograms



HAZARD STATEMENTS:

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280E Wear protective gloves.
P272A Contaminated work clothing must not be allowed out of the workplace.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P321 Specific treatment (see Notes to Physician on this label).

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Cristobalite	14464-46-1	20 - 40
Vinyl-polydimethyl siloxane	68083-19-2	30 - 40
Dimethyl methyl hydrogen silicone fluid	68037-59-2	10 - 20
Silica, vitreous	60676-86-0	1 - 10
Polyethyleneglycol, siloxane terminated	27306-78-1	1 - 10
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	67762-90-7	1 - 10
Allyltrimethylsilane	762-72-1	< 5
Fluorinated polyether	Trade Secret	< 5
Tridymite	15468-32-3	< 2
Cornmint oil	68917-18-0	< 0.5
Quartz	14808-60-7	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Cristobalite	14464-46-1	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Silica, crystalline (airborne particles of respirable size)	14464-46-1	New Zealand WES	TWA(as respirable dust)(8 hours): 0.1 mg/m3	
Quartz	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Silica, crystalline (airborne particles of respirable size)	14808-60-7	New Zealand WES	TWA(as respirable dust)(8 hours): 0.1 mg/m3	
Silica, crystalline (airborne particles of respirable size)	15468-32-3	New Zealand WES	TWA(as respirable dust)(8 hours): 0.1 mg/m3	
Silica, vitreous	60676-86-0	New Zealand WES	TWA(as respirable dust)(8 hours): 0.2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CELL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

Respiratory protection is not required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Solid.
Specific Physical Form:	Paste
Appearance/Odour	mint scented, white coloured paste
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	1.1 g/cm ³ - 1.3 g/cm ³
Relative density	1.1 - 1.3 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>Not applicable.</i>
Percent volatile	<i>Not applicable.</i>
VOC less H₂O & exempt solvents	<i>Not applicable.</i>

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Amines.
 Strong acids.
 Strong bases.
 Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:
 Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Vinyl-polydimethyl siloxane	Dermal	Rabbit	LD50 > 15,440 mg/kg

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

Vinyl-polydimethyl siloxane	Ingestion	Rat	LD50 > 15,440 mg/kg
Cristobalite	Dermal		LD50 estimated to be > 5,000 mg/kg
Cristobalite	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dimethyl methyl hydrogen silicone fluid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Dimethyl methyl hydrogen silicone fluid	Ingestion	Rat	LD50 > 2,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Polyethyleneglycol, siloxane terminated	Dermal	Rabbit	LD50 > 2,000 mg/kg
Polyethyleneglycol, siloxane terminated	Inhalation-Dust/Mist (4 hours)	Rat	LC50 2 mg/l
Polyethyleneglycol, siloxane terminated	Ingestion	Rat	LD50 > 2,000 mg/kg
Allyltrimethylsilane	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Allyltrimethylsilane	Ingestion	similar compounds	LD50 estimated to be 2,000 - 5,000 mg/kg
Fluorinated polyether	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Fluorinated polyether	Ingestion	Rat	LD50 > 1,000 mg/kg
Tridymite	Dermal		LD50 estimated to be > 5,000 mg/kg
Tridymite	Ingestion		LD50 estimated to be > 5,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
Cornmint oil	Dermal	Rabbit	LD50 > 5,000 mg/kg
Cornmint oil	Ingestion	Rat	LD50 1,240 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Vinyl-polydimethyl siloxane	Rabbit	No significant irritation
Cristobalite	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Polyethyleneglycol, siloxane terminated	Rabbit	No significant irritation
Tridymite	Professional judgement	No significant irritation
Quartz	Professional judgement	No significant irritation
Cornmint oil	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Vinyl-polydimethyl siloxane	Rabbit	Mild irritant
Silica, vitreous	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Polyethyleneglycol, siloxane terminated	Rabbit	Severe irritant
Cornmint oil	In vitro data	Severe irritant

Skin Sensitisation

Name	Species	Value
Silica, vitreous	Human and animal	Not classified
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified
Polyethyleneglycol, siloxane terminated	Guinea pig	Not classified
Cornmint oil	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Cristobalite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cristobalite	In vivo	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	In Vitro	Not mutagenic
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic
Polyethyleneglycol, siloxane terminated	In Vitro	Not mutagenic
Polyethyleneglycol, siloxane terminated	In vivo	Not mutagenic
Tridymite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Tridymite	In vivo	Some positive data exist, but the data are not sufficient for classification
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Cristobalite	Inhalation	Human and animal	Carcinogenic.
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Tridymite	Inhalation	Human and animal	Carcinogenic.
Quartz	Inhalation	Human and animal	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Polyethyleneglycol, siloxane terminated	Ingestion	Not classified for reproduction and/or development	Rat	NOAEL 450 mg/kg/day	prematuring & during gestation
Fluorinated polyether	Ingestion	Not classified for reproduction and/or development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Fluorinated polyether	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Fluorinated polyether	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Cristobalite	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Fluorinated polyether	Ingestion	auditory system heart endocrine system hematopoietic system liver immune system muscles nervous system eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Tridymite	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Cristobalite	14464-46-1		Data not available or insufficient for classification			
Vinyl-polydimethyl siloxane	68083-19-2		Data not available or insufficient for classification			
Dimethyl methyl hydrogen silicone fluid	68037-59-2		Data not available or insufficient for classification			
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Polyethyleneglycol, siloxane terminated	27306-78-1		Data not available or insufficient for classification			
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	67762-90-7		Data not available or insufficient for classification			
Allyltrimethylsilane	762-72-1		Data not available or insufficient for classification			
Fluorinated polyether	Trade Secret		Data not available or insufficient for classification			
Tridymite	15468-32-3		Data not available or insufficient for			

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

			classification			
Cornmint oil	68917-18-0		Data not available or insufficient for classification			
Quartz	14808-60-7		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Cristobalite	14464-46-1	Data not available- insufficient			N/A	
Vinyl-polydimethyl siloxane	68083-19-2	Data not available- insufficient			N/A	
Dimethyl methyl hydrogen silicone fluid	68037-59-2	Data not available- insufficient			N/A	
Silica, vitreous	60676-86-0	Data not available- insufficient			N/A	
Polyethyleneglycol, siloxane terminated	27306-78-1	Data not available- insufficient			N/A	
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	67762-90-7	Data not available- insufficient			N/A	
Allyltrimethylsilane	762-72-1	Estimated Biodegradation	28 days	BOD	9 % BOD/ThBOD	OECD 301F - Manometric respirometry
Fluorinated polyether	Trade Secret	Data not available- insufficient			N/A	
Tridymite	15468-32-3	Data not available- insufficient			N/A	
Cornmint oil	68917-18-0	Data not available- insufficient			N/A	
Quartz	14808-60-7	Data not available- insufficient			N/A	

12.3 : Bioaccumulative potential

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Cristobalite	14464-46-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Vinyl-polydimethyl siloxane	68083-19-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl methyl hydrogen silicone fluid	68037-59-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyethyleneglycol, siloxane terminated	27306-78-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Allyltrimethylsilane	762-72-1	Estimated Bioconcentration		Bioaccumulation factor	269	Estimated: Bioconcentration factor
Fluorinated polyether	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tridymite	15468-32-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cornmint oil	68917-18-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval number	HSR002558
Group standard name	Dental Products (Subsidiary Hazard) Group Standard 2017
HSNO Hazard classification	Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT BASE

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for a HSNO 6.6A, 6.8A, 6.9A, 8.3A, 9.1D substance)
Secondary containment	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for a HSNO 6.6A, 6.8A, 6.9A, 8.3A, 9.1D substance)
Tracking	Not required
Warning signage	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 8.3A, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for a HSNO 6.1D or 9.1D substance)

SECTION 16: Other information**Revision information:**

Complete document review.

Document group:	31-4864-0	Version number:	2.00
Issue Date:	10/12/2018	Supersedes date:	21/04/2013

Key to abbreviations and acronyms**GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>



Safety Data Sheet

© 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 31-4875-6 **Version number:** 2.00
Issue Date: 10/12/2018 **Supersedes date:** 21/04/2013

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Impression Material

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
No GHS Equivalent	9.4C Terrestrial invertebrate toxicity

2.2. Label elements

SIGNAL WORD

Not applicable.

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

Symbols:

Not applicable.

HAZARD STATEMENTS:

H443 Harmful to terrestrial invertebrates.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Vinyl terminated polydimethylsiloxane	68083-19-2	40 - 60
Cristobalite	14464-46-1	20 - 40
Silica, vitreous	60676-86-0	5 - 20
Poly(dimethylsiloxane)	63148-62-9	1 - 10
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	67762-90-7	1 - 10
Tridymite	15468-32-3	< 5
Cobalt aluminate blue spinel	1345-16-0	< 0.5
Quartz	14808-60-7	< 0.3

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Cobalt, inorganic compounds	1345-16-0	ACGIH	TWA(as Co):0.02 mg/m ³	A3: Confirmed animal carcinogen.
Cristobalite	14464-46-1	ACGIH	TWA(respirable fraction):0.025 mg/m ³	A2: Suspected human carcin.
Silica, crystalline (airborne particles of respirable size)	14464-46-1	New Zealand WES	TWA(as respirable dust)(8 hours): 0.1 mg/m ³	Class-subclass 6.7, carc HCA
Quartz	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m ³	A2: Suspected human carcin.
Silica, crystalline (airborne particles of respirable size)	14808-60-7	New Zealand WES	TWA(as respirable dust)(8 hours): 0.1 mg/m ³	Class-subclass 6.7, carc HCA
Silica, crystalline (airborne particles of respirable size)	15468-32-3	New Zealand WES	TWA(as respirable dust)(8 hours): 0.1 mg/m ³	Class-subclass 6.7, carc HCA
Silica, vitreous	60676-86-0	New Zealand WES	TWA(as respirable dust)(8 hours): 0.2 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Solid.

Specific Physical Form:

Paste

Appearance/Odour

Slight characteristic odour, white colour paste.

Odour threshold

No data available.

pH

No data available.

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	1.2 - 1.4 g/m ³
Relative density	1.2 - 1.4 [Ref.Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>Not applicable.</i>
Percent volatile	<i>Not applicable.</i>
VOC less H ₂ O & exempt solvents	<i>Not applicable.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Vinyl terminated polydimethylsiloxane	Dermal	Rabbit	LD50 > 15,440 mg/kg
Vinyl terminated polydimethylsiloxane	Ingestion	Rat	LD50 > 15,440 mg/kg
Cristobalite	Dermal		LD50 estimated to be > 5,000 mg/kg
Cristobalite	Ingestion		LD50 estimated to be > 5,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Poly(dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Tridymite	Dermal		LD50 estimated to be > 5,000 mg/kg
Tridymite	Ingestion		LD50 estimated to be > 5,000 mg/kg
Cobalt aluminate blue spinel	Dermal		LD50 estimated to be > 5,000 mg/kg
Cobalt aluminate blue spinel	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

Quartz	Ingestion	LD50 estimated to be > 5,000 mg/kg
--------	-----------	------------------------------------

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Vinyl terminated polydimethylsiloxane	Rabbit	No significant irritation
Cristobalite	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Poly(dimethylsiloxane)	Rabbit	No significant irritation
Tridymite	Professional judgement	No significant irritation
Quartz	Professional judgement	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Vinyl terminated polydimethylsiloxane	Rabbit	Mild irritant
Silica, vitreous	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Rabbit	No significant irritation
Poly(dimethylsiloxane)	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Silica, vitreous	Human and animal	Not classified
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Cristobalite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cristobalite	In vivo	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	In Vitro	Not mutagenic
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	In Vitro	Not mutagenic
Tridymite	In Vitro	Some positive data exist, but the data are not sufficient for classification
Tridymite	In vivo	Some positive data exist, but the data are not sufficient for classification
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
--------	---------	--

Carcinogenicity

Name	Route	Species	Value
Cristobalite	Inhalation	Human and animal	Carcinogenic.
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Tridymite	Inhalation	Human and animal	Carcinogenic.
Quartz	Inhalation	Human and animal	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Cristobalite	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl)propyl ester, hydrolysis products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Tridymite	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Ecotoxic to terrestrial invertebrates**

9.4C Terrestrial invertebrate toxicity

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Vinyl terminated polydimethylsiloxane	68083-19-2		Data not available or insufficient for classification			
Cristobalite	14464-46-1		Data not available or insufficient for classification			
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Poly(dimethylsiloxane)	63148-62-9		Data not available or insufficient for classification			
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	67762-90-7		Data not available or insufficient for classification			
Tridymite	15468-32-3		Data not available or insufficient for classification			
Quartz	14808-60-7		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Vinyl	68083-19-2	Data not			N/A	

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

terminated polydimethylsiloxane		availbl-insufficient				
Cristobalite	14464-46-1	Data not availbl-insufficient			N/A	
Silica, vitreous	60676-86-0	Data not availbl-insufficient			N/A	
Poly(dimethylsiloxane)	63148-62-9	Data not availbl-insufficient			N/A	
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis products with silica	67762-90-7	Data not availbl-insufficient			N/A	
Tridymite	15468-32-3	Data not availbl-insufficient			N/A	
Cobalt aluminate blue spinel	1345-16-0	Data not availbl-insufficient			N/A	
Quartz	14808-60-7	Data not availbl-insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Vinyl terminated polydimethylsiloxane	68083-19-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cristobalite	14464-46-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 3-(trimetoxysilyl) propyl ester, hydrolysis	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

products with silica						
Tridymite	15468-32-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cobalt aluminate blue spinel	1345-16-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information**New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.

3M™ ESPE™ IMPRINT™ 4 SUPER QUICK LIGHT CATALYST

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval number HSR002558
Group standard name Dental Products (Subsidiary Hazard) Group Standard 2017
HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	Not required
Secondary containment	Not required
Tracking	Not required
Warning signage	Not required

SECTION 16: Other information**Revision information:**

Complete document review.

Document group:	31-4875-6	Version number:	2.00
Issue Date:	10/12/2018	Supersedes date:	21/04/2013

Key to abbreviations and acronyms

GHS means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>