



Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: Ostron 100 Liquid

Manufacturer: GC Corporation

SDS Expiry: 30 November 2025

Supplier Details: Henry Schein New Zealand

23 William Pickering Drive, Albany

PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –

0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 6

HSNO Group Standard: Dental Products Flammable Group Standard 2017 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared on 8 January 2021

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

# 1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: GC Ostron 100 Liquid
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet

Henry Schein Dental 23 William Pickering Drive, Albany Auckland 0632, NEW ZEALAND

PO Box 101140, NSMC Auckland 0745, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

# 2 Hazards identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Acute Tox. 5 H333 May be harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

*N,N-dimethyl-p-toluidine* 

· Hazard statements

Highly flammable liquid and vapour.

May be harmful if inhaled.

Causes skin irritation.

(Contd. on page 2)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 1)

May cause an allergic skin reaction.

May cause respiratory irritation.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
	Methyl methacrylate	75-<90%
EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Acute Tox. 5, H333	
CAS: 8012-95-1 EINECS: 232-384-2	Paraffin oils	5-<10%
	N,N-dimethyl-p-toluidine	0.5-<1%
EINECS: 202-805-4	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Flam. Liq. 4, H227; Aquatic Chronic 3, H412	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- · Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 2)

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

 $Dispose\ of\ the\ material\ collected\ according\ to\ regulations.$ 

· Reference to other sections

See Section 7 for information on safe handling.

 $See \ Section \ 8 \ for \ information \ on \ personal \ protection \ equipment.$ 

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

80-62-6 Methyl methacrylate		
WES (New Zealand)	Short-term value: 416 mg/m³, 100 ppm	
	Long-term value: 208 mg/m³, 50 ppm	
	skin	
IOELV (European Union)	Short-term value: 100 ppm	
	Long-term value: 50 ppm	
8012-95-1 Paraffin oils		
WES (New Zealand)	Short-term value: 10 mg/m³	
	Long-term value: 5 mg/m³	
DNELs		
80-62-6 Methyl methacryl	ate	
Dermal DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)	
Inhalative DNEL inhalation	on 208 mg/m3 (air) (worker, l. te., syst.)	

PNEC Aqua | 152.59 µg/L (freshwater)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· Respiratory protection: Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 4)

### · Protection of hands:



#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

· Information on basic physical and che	mical properties
· General Information	micui properties
· Appearance:	
Form:	Liquid
Colour:	Clear
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	re: 100 °C
· Flash point:	10 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	$0.9 \ g/cm^3$
Relative density	Not determined.
· Vapour density	Not determined.

(Contd. on page 6)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

	(Contd. o	of page 5
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC (EC)	$0.0 \ \mathrm{g/l}$	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:		
80-62-6 Methyl methacrylate		
Oral	LD50	6,000 mg/kg (rabbit)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))
99-97-8 N,N-dimethyl-p-toluidine		
Oral	LD50	1,650 mg/kg (rat (f+m))
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	1.4 mg/l (rat (f+m))

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· Repeated dose toxicity No further relevant information available.

(Contd. on page 7)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 6)

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
No further relevant information available.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

#### 99-97-8 N,N-dimethyl-p-toluidine

LC50/96h 46 mg/L (fish)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport inform	ากรากท

· UN-Number	
· ADR, IMDG, IATA	UN1247

· UN proper shipping name

· ADR

1247 METHYL METHACRYLATE MONOMER,
STABILIZED

· IMDG, IATA

1247 METHYL METHACRYLATE MONOMER, STABILIZED

- · Transport hazard class(es)
- $\cdot ADR$



Class 3 (F1) Flammable liquids.

(Contd. on page 8)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

	(Contd. of page
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F- $E$ , $S$ - $D$
Stowage Category	C
Stowage Code	SWI Protected from sources of heat.
	SW2 Clear of living quarters.
Transport in bulk according to Annex II of Mary	
and the IBC Code	Not applicable.
Transport/Additional information:	Temperature control is not required, in regards to Special Provision 386. Product uses chemical stabilization.
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2 D/E
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER
	STABILIZED, 3, II

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

80-62-6 Methyl methacrylate

HSR001195

(Contd. on page 9)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 8)

99-97-8 N,N-dimethyl-p-toluidine

HSR003833

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

2 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

*N,N-dimethyl-p-toluidine* 

#### · Hazard statements

Highly flammable liquid and vapour.

May be harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

### · Relevant phrases

H225 Highly flammable liquid and vapour.

H227 Combustible liquid.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental

(Contd. on page 10)

Printing date 30.11.2020 Version number 3 Revision: 30.11.2020

Trade name: GC Ostron 100 Liquid

(Contd. of page 9)

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 3: Acute toxicity - oral - Category 3

Acute Tox. 5: Acute toxicity - inhalation - Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

#### ·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

### \* Data compared to the previous version altered.

This version replaces all previous versions.

#### Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.