

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: Pola Luminare

Manufacturer: SDI Limited

SDS Expiry: 1 November 2024

Supplier Details: Henry Schein New Zealand  
23 William Pickering Drive, Albany  
PO Box 101 140, North Shore, Auckland 0745  
Ph. 0800 808 855  
[www.henryschein.co.nz](http://www.henryschein.co.nz)

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –  
0800POISON/0800764766 (24 Hours)  
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 3 / 8

HSNO Group Standard: Dental Products Flammable Group Standard 2020 HSR002556

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared - June 2021

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



## Pola Luminat

### SDI Limited

Version No: 4.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 01/11/2019

Print Date: 25/03/2020

L.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | Pola Luminat   |
| Synonyms                      | Not Available  |
| Proper shipping name          | ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) |
| Other means of identification | Not Available  |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | To remove discoloration of teeth, under the supervision of a dentist. |
|--------------------------|---|

### Details of the supplier of the safety data sheet

| Registered company name | SDI Limited                                      | SDI (North America) Inc.                            | SDi   |
|-------------------------|--|---|---|
| Address                 | 3-15 Brunson Street Bayswater VIC 3153 Australia | 1279 Hamilton Parkway Itasca IL 60143 United States | Rua Dr. Virgilio de Carvalho Pinto, 612 Pinheiros, Sao Paulo 05415-020 Brazil |
| Telephone               | +61 3 8727 7111 (Business Hours)                 | +1 630 361 9200 (Business hours) 1 800 228 5166     | +55 11 3092 7100 (Business Hours)   |
| Fax                     | +61 3 8727 7222                                  | +1 630 361 9222                                     | +55 11 3092 7101  |
| Website                 | www.sdi.com.au                                   | http://www.sdi.com.au                               | http://www.sdi.com.au/  |
| Email                   | info@sdi.com.au                                  | USA.Canada@sdi.com.au                               | Brasil@sdi.com.au   |

### Emergency telephone number


| Association / Organisation        | SDI Limited           | SDi             |
|-----------------------------------|-----------------------|-----------------|
| Emergency telephone numbers       | +61 3 8727 7111       | +61 3 8727 7111 |
| Other emergency telephone numbers | ray.cahill@sdi.com.au | Not Available   |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

|                    |  |
|--------------------|--|
| Poisons Schedule   | S5   |
| Classification [1] | Flammable Liquid Category 2, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1                                    |
| Legend:            | 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

### Label elements

|                     |   |
|---------------------|---|
| Hazard pictogram(s) |  |
| SIGNAL WORD         | DANGER  |

### Hazard statement(s)

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.      |
| H314 | Causes severe skin burns and eye damage. |

### Precautionary statement(s) Prevention

|      |  |
|------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking.         |
| P233 | Keep container tightly closed.   |
| P260 | Do not breathe mist/vapours/spray.   |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P240 | Ground/bond container and receiving equipment.                             |

Continued...

## Pola Luminate

|      |   |
|------|---|
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| P242 | Use only non-sparking tools.  |
| P243 | Take precautionary measures against static discharge.                             |

## Precautionary statement(s) Response

|                |  |
|----------------|--|
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.   |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.                       |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310           | Immediately call a POISON CENTER or doctor/physician.  |
| P321           | Specific treatment (see advice on this label).   |
| P370+P378      | In case of fire: Use alcohol resistant foam or fine spray/water fog for extinction.  |
| P363           | Wash contaminated clothing before reuse.   |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |

## Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405      | Store locked up.                             |

## Precautionary statement(s) Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## Substances

See section below for composition of Mixtures

## Mixtures

| CAS No    | %[weight] | Name              |
|-----------|-----------|-------------------|
| 64-17-5   | 48        | ethanol           |
| 7722-84-1 | 6         | hydrogen peroxide |

## SECTION 4 FIRST AID MEASURES

## Description of first aid measures

|              |  |
|--------------|--|
| Eye Contact  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| Inhalation   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>  |
| Ingestion    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul>   |

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5 FIREFIGHTING MEASURES

## Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

## Special hazards arising from the substrate or mixture

## Pola Luminate

|                                |  |
|--------------------------------|--|
| <b>Fire Incompatibility</b>    | None known   |
| <b>Advice for firefighters</b> |  |
| <b>Fire Fighting</b>           | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Fight fire from a safe distance, with adequate cover.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>Do not</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| <b>Fire/Explosion Hazard</b>   | <p>Combustion products include:<br/>carbon dioxide (CO<sub>2</sub>)<br/>other pyrolysis products typical of burning organic material.</p> <ul style="list-style-type: none"> <li>▶ Liquid and vapour are flammable.</li> <li>▶ Moderate fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Moderate explosion hazard when exposed to heat or flame.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>May emit poisonous fumes.<br/>May emit corrosive fumes.</p>  |
| <b>HAZCHEM</b>                 | *2YE   |

**SECTION 6 ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> <li>▶ Collect residues in a flammable waste container.</li> </ul>  |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse /absorb vapour.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Use only spark-free shovels and explosion proof equipment.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 HANDLING AND STORAGE****Precautions for safe handling**

|                      |  |
|----------------------|--|
| <b>Safe handling</b> | <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> </ul> |
|----------------------|--|

Continued...

## Pola Luminate

|                          |  |
|--------------------------|--|
|                          | <ul style="list-style-type: none"> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul>   |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of overexposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT allow material to contact humans, exposed food or food utensils.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Working clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> <li>▶ Avoid generation of static electricity. Earth all lines and equipment.</li> </ul> <p>Use spark-free tools when handling<br/>Store in a dry and well-ventilated area, away from heat and sunlight.<br/>Store between 5 and 25 deg. C.</p> |

**Conditions for safe storage, including any incompatibilities**

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | ▶ <b>DO NOT repack.</b> Use containers supplied by manufacturer only. |
| <b>Storage incompatibility</b> | ▶ Avoid strong bases.   |

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

| Source                       | Ingredient        | Material name     | TWA                               | STEL          | Peak          | Notes         |
|------------------------------|-------------------|-------------------|-----------------------------------|---------------|---------------|---------------|
| Australia Exposure Standards | ethanol           | Ethyl alcohol     | 1000 ppm / 1880 mg/m <sup>3</sup> | Not Available | Not Available | Not Available |
| Australia Exposure Standards | hydrogen peroxide | Hydrogen peroxide | 1 ppm / 1.4 mg/m <sup>3</sup>     | Not Available | Not Available | Not Available |

**EMERGENCY LIMITS**

| Ingredient        | Material name            | TEEL-1        | TEEL-2        | TEEL-3        |
|-------------------|--------------------------|---------------|---------------|---------------|
| ethanol           | Ethanol: (Ethyl alcohol) | Not Available | Not Available | 15000* ppm    |
| hydrogen peroxide | Hydrogen peroxide        | Not Available | Not Available | Not Available |


| Ingredient        | Original IDLH | Revised IDLH  |
|-------------------|---------------|---------------|
| ethanol           | 3,300 ppm     | Not Available |
| hydrogen peroxide | 75 ppm        | Not Available |

**MATERIAL DATA****Exposure controls**

|   |   |                        |            |  |                                 |   |                               |  |                               |                        |  |                        |
|---|---|------------------------|------------|--|---------------------------------|---|-------------------------------|--|-------------------------------|------------------------|--|------------------------|
| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> |                        |            |  |                                 |   |                               |  |                               |                        |  |                        |
|   | <table border="0" style="width: 100%;"> <tr> <td style="width: 80%;">Type of Contaminant:</td> <td style="border-left: 1px dashed black; width: 20%; text-align: center;">Air Speed:</td> </tr> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td style="border-left: 1px dashed black; text-align: center;">0.25-0.5 m/s<br/>(50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td style="border-left: 1px dashed black; text-align: center;">0.5-1 m/s<br/>(100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td style="border-left: 1px dashed black; text-align: center;">1-2.5 m/s<br/>(200-500 f/min.)</td> </tr> </table> <p>Within each range the appropriate value depends on:</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Lower end of the range</td> <td style="border-left: 1px dashed black; width: 10%;"></td> <td style="width: 40%;">Upper end of the range</td> </tr> </table>                               | Type of Contaminant:   | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s<br>(50-100 f/min.) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s<br>(200-500 f/min.) | Lower end of the range |  | Upper end of the range |
| Type of Contaminant:  | Air Speed:  |                        |            |  |                                 |   |                               |  |                               |                        |  |                        |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s<br>(50-100 f/min.)   |                        |            |  |                                 |   |                               |  |                               |                        |  |                        |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)   |                        |            |  |                                 |   |                               |  |                               |                        |  |                        |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s<br>(200-500 f/min.)   |                        |            |  |                                 |   |                               |  |                               |                        |  |                        |
| Lower end of the range  |   | Upper end of the range |            |  |                                 |   |                               |  |                               |                        |  |                        |

Continued...

## Pola Luminate

|                         |   |  |
|-------------------------|---|--|
|                         | 1: Room air currents minimal or favourable to capture<br>2: Contaminants of low toxicity or of nuisance value only.<br>3: Intermittent, low production.<br>4: Large hood or large air mass in motion  | 1: Disturbing room air currents<br>2: Contaminants of high toxicity<br>3: High production, heavy use<br>4: Small hood-local control only |
|                         | <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>   |  |
| Personal protection     |    |  |
| Eye and face protection | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul> |  |
| Skin protection         | See Hand protection below   |  |
| Hands/feet protection   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul>  |  |
| Body protection         | See Other protection below  |  |
| Other protection        | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> </ul>   |  |

## Respiratory protection

Type AB Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | AB-AUS               | -                    | AB-PAPR-AUS / Class 1  |
| up to 50 x ES                      | -                    | AB-AUS / Class 1     | -                      |
| up to 100 x ES                     | -                    | AB-2                 | AB-PAPR-2 ^            |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|  |   |   |                |
|--|---|---|----------------|
| Appearance                                   | Cloudy low viscosity gel with spearmint odour, spearmint taste, mixes with water. |   |                |
| Physical state                               | Gel   | Relative density (Water = 1)            | 0.94           |
| Odour  | Not Available   | Partition coefficient n-octanol / water | Not Available  |
| Odour threshold                              | Not Available   | Auto-ignition temperature (°C)          | Not Available  |
| pH (as supplied)                             | 5.9-6.3   | Decomposition temperature               | Not Available  |
| Melting point / freezing point (°C)          | Not Available   | Viscosity (cSt)                         | Not Available  |
| Initial boiling point and boiling range (°C) | Not Available   | Molecular weight (g/mol)                | Not Applicable |
| Flash point (°C)                             | Not Available   | Taste                                   | Not Available  |
| Evaporation rate                             | Not Available   | Explosive properties                    | Not Available  |
| Flammability                                 | Not Available   | Oxidising properties                    | Not Available  |
| Upper Explosive Limit (%)                    | Not Available   | Surface Tension (dyn/cm or mN/m)        | Not Available  |
| Lower Explosive Limit (%)                    | Not Available   | Volatile Component (%vol)               | Not Available  |
| Vapour pressure (kPa)                        | Not Available   | Gas group                               | Not Available  |
| Solubility in water                          | Miscible  | pH as a solution (1%)                   | Not Available  |

Continued...

## Pola Luminate

Vapour density (Air = 1) Not Available

VOC g/L Not Available

## SECTION 10 STABILITY AND REACTIVITY

|                                    |  |
|------------------------------------|--|
| Reactivity                         | See section 7  |
| Chemical stability                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> Solutions of hydrogen peroxide slowly decompose, releasing oxygen, and so are often stabilised by the addition of acetanilide, etc. |
| Possibility of hazardous reactions | See section 7  |
| Conditions to avoid                | See section 7  |
| Incompatible materials             | See section 7  |
| Hazardous decomposition products   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|              |  |
|--------------|--|
| Inhaled      | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.  |
| Ingestion    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. |
| Skin Contact | The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  |
| Eye          | Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.  |
| Chronic      | Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.  |

|                   |   |  |
|-------------------|---|--|
| Pola Luminate     | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                   | Not Available   | Not Available  |
| ethanol           | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                   | Inhalation (rat) LC50: 124.7 mg/l/4H <sup>[2]</sup>   | Eye (rabbit): 500 mg SEVERE                              |
|                   | Oral (rat) LD50: ≈1501 mg/kg <sup>[2]</sup>   | Eye (rabbit):100mg/24hr-moderate                         |
|                   |   | Eye: adverse effect observed (irritating) <sup>[1]</sup> |
|                   |   | Skin (rabbit):20 mg/24hr-moderate                        |
|                   |   | Skin (rabbit):400 mg (open)-mild                         |
|                   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup>  |  |
| hydrogen peroxide | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                   | dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>   | Not Available  |
|                   | Inhalation (rat) LC50: 2 mg/l/4H <sup>[2]</sup>   |  |
|                   | Oral (rat) LD50: >225 mg/kg <sup>[2]</sup>  |  |
| <b>Legend:</b>    | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |  |

|                   |   |
|-------------------|---|
| ETHANOL           | The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.  |
| HYDROGEN PEROXIDE | No significant acute toxicological data identified in literature search.<br><br>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. |

Continued...

## Pola Luminat

Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

For hydrogen peroxide:

Hazard increases with peroxide concentration, high concentrations contain an additive stabiliser.

**Pharmacokinetics**

Hydrogen peroxide is a normal product of metabolism. It is readily decomposed by catalase in normal cells. In experimental animals exposed to hydrogen peroxide, target organs affected include the lungs, intestine, thymus, liver, and kidney, suggesting its distribution to those sites.

Hydrogen peroxide has been detected in breath.

- ▶ Absorption: Hydrogen peroxide is decomposed in the bowel before absorption. When applied to tissue, solutions of hydrogen peroxide have poor penetrability.
- ▶ Distribution: Hydrogen peroxide is produced metabolically in intact cells and tissues. It is formed by reduction of oxygen either directly in a two-electron transfer reaction, often catalysed by flavoproteins, or by an initial one-electron step to O<sub>2</sub> followed by dismutation to hydrogen peroxide.
- ▶ Hydrogen peroxide has been detected in serum and in intact liver. based on the results of toxicity studies, the lungs, intestine, thymus, liver, and kidney may be distribution sites. In rabbits and cats that died after intravenous administration of hydrogen peroxide, the lungs were pale and emphysematous. Following intraperitoneal injection of hydrogen peroxide in mice, pyknotic nuclei were induced in the intestine and thymus (IARC 1985). Degeneration of hepatic and renal tubular epithelial tissue was observed following oral administration of hydrogen peroxide to mice.
- ▶ Metabolism: Glutathione peroxidase, responsible for decomposing hydrogen peroxide, is present in normal human tissues (IARC 1985). When hydrogen peroxide comes in contact with catalase, an enzyme found in blood and most tissues, it rapidly decomposes into oxygen and water.
- ▶ Excretion: Hydrogen peroxide has been detected in human breath at levels ranging from 1.0+/-0.5 g/L to 0.34+/-0.17 g/L.

**Carcinogenicity**

Gastric and duodenal lesions including adenomas, carcinomas, and adenocarcinomas have been observed in mice treated orally with hydrogen peroxide. Marked strain differences in the incidence of tumors have been observed. Papilloma development has been observed in mice treated by dermal application.

**Genotoxicity**

Hydrogen peroxide induced DNA damage, sister chromatid exchanges and chromosomal aberrations in mammalian cells *in vitro*. Hydrogen peroxide induced DNA damage in bacteria (*E. coli*), and was mutagenic to bacteria (*Salmonella typhimurium*) and the fungi, *Neurospora crassa* and *Aspergillus chevallieri*, but not to *Streptomyces griseoflavus*. It was not mutagenic to *Drosophila melanogaster* or to mammalian cells *in vitro*.

**Developmental Toxicity**

Malformations have been observed in chicken embryos treated with hydrogen peroxide, but experiments with mice and rats have been negative. Female rats that received 0.45% hydrogen peroxide (equivalent to approximately 630 mg/kg/day) as the sole drinking fluid for five weeks produced normal litters when mated with untreated males.

Doses of 1.4 to 11 mol/egg hydrogen peroxide (purity 30%) dissolved in water were injected into the airspace of groups of 20-30 white leghorn chicken eggs on day 3 of incubation.

Embryos were examined on day 14. The incidence of embryonic deaths and malformations was dose-related and detected at doses of 2.8 mol/egg and above. The combined ED<sub>50</sub> was 2.7 mol/egg.

**Reproductive Toxicity**

A 1% solution of hydrogen peroxide (equivalent to 1900 mg/kg/day) given as the sole drinking fluid to three-month-old male mice for 7-28 days did not cause infertility.

The substance is classified by IARC as Group 3:

**NOT** classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✗ | Carcinogenicity          | ✗ |
| Skin Irritation/Corrosion         | ✓ | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation     | ✓ | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity                      | ✗ | Aspiration Hazard        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

**SECTION 12 ECOLOGICAL INFORMATION****Toxicity**

| Pola Luminat      | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|-------------------|---------------|--------------------|-------------------------------|---------------|---------------|
|                   | Not Available | Not Available      | Not Available                 | Not Available | Not Available |
| ethanol           | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|                   | LC50          | 96                 | Fish                          | 11-mg/L       | 2             |
|                   | EC50          | 48                 | Crustacea                     | 2mg/L         | 4             |
|                   | EC50          | 96                 | Algae or other aquatic plants | 17.921mg/L    | 4             |
|                   | NOEC          | 2016               | Fish                          | 0.000375mg/L  | 4             |
| hydrogen peroxide | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|                   | LC50          | 96                 | Fish                          | 0.020mg/L     | 3             |
|                   | EC50          | 48                 | Crustacea                     | 2mg/L         | 2             |
|                   | EC50          | 72                 | Algae or other aquatic plants | 0.71mg/L      | 4             |
|                   | EC0           | 24                 | Crustacea                     | 1.1mg/L       | 2             |
|                   | NOEC          | 192                | Fish                          | 0.028mg/L     | 4             |

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite



## Pola Luminate

V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

| Ingredient        | Persistence: Water/Soil     | Persistence: Air            |
|-------------------|-----------------------------|-----------------------------|
| ethanol           | LOW (Half-life = 2.17 days) | LOW (Half-life = 5.08 days) |
| hydrogen peroxide | LOW                         | LOW                         |

## Bioaccumulative potential

| Ingredient        | Bioaccumulation       |
|-------------------|-----------------------|
| ethanol           | LOW (LogKOW = -0.31)  |
| hydrogen peroxide | LOW (LogKOW = -1.571) |

## Mobility in soil

| Ingredient        | Mobility         |
|-------------------|------------------|
| ethanol           | HIGH (KOC = 1)   |
| hydrogen peroxide | LOW (KOC = 14.3) |

## SECTION 13 DISPOSAL CONSIDERATIONS

## Waste treatment methods

|                              |  |
|------------------------------|--|
| Product / Packaging disposal | <ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|------------------------------|--|

## SECTION 14 TRANSPORT INFORMATION

## Labels Required

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant | NO  |
| HAZCHEM          | *2YE  |

## Land transport (ADG)

|                              |  |
|------------------------------|--|
| UN number                    | 1170   |
| UN proper shipping name      | ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) |
| Transport hazard class(es)   | Class : 3<br>Subrisk : Not Applicable                                |
| Packing group                | II   |
| Environmental hazard         | Not Applicable   |
| Special precautions for user | Special provisions : 144<br>Limited quantity : 1 L                   |

## Air transport (ICAO-IATA / DGR)

|                            |  |
|----------------------------|--|
| UN number                  | 1170   |
| UN proper shipping name    | Ethanol or Ethanol. solution   |
| Transport hazard class(es) | ICAO/IATA Class : 3<br>ICAO / IATA Subrisk : Not Applicable<br>ERG Code : 3L |
| Packing group              | II   |

## Pola Luminate

|                                     |   |             |
|-------------------------------------|---|-------------|
| <b>Environmental hazard</b>         | Not Applicable  |             |
| <b>Special precautions for user</b> | Special provisions  | A3 A58 A180 |
|                                     | Cargo Only Packing Instructions                           | 364         |
|                                     | Cargo Only Maximum Qty / Pack                             | 60 L        |
|                                     | Passenger and Cargo Packing Instructions                  | 353         |
|                                     | Passenger and Cargo Maximum Qty / Pack                    | 5 L         |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions | Y341        |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack            | 1 L         |

## Sea transport (IMDG-Code / GGVSee)

|                                     |  |                |
|-------------------------------------|--|----------------|
| <b>UN number</b>                    | 1170   |                |
| <b>UN proper shipping name</b>      | ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) |                |
| <b>Transport hazard class(es)</b>   | IMDG Class   | 3              |
|                                     | IMDG Subrisk   | Not Applicable |
| <b>Packing group</b>                | II   |                |
| <b>Environmental hazard</b>         | Not Applicable   |                |
| <b>Special precautions for user</b> | EMS Number   | F-E , S-D      |
|                                     | Special provisions   | 144            |
|                                     | Limited Quantities   | 1 L            |

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

If packed as Chemical kits the following classification may be considered if all ICAO/IATA transport requirements are met: Chemical Kit UN3316 - Class 9, SP A44 &amp; A163.

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## ETHANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards  
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix B (Part 3)

## HYDROGEN PEROXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards  
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Inventory of Chemical Substances (AICS)  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6  
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

## National Inventory Status

| National Inventory            | Status   |
|-------------------------------|--|
| Australia - AICS              | Yes  |
| Canada - DSL                  | Yes  |
| Canada - NDSL                 | No (hydrogen peroxide; ethanol)  |
| China - IECSC                 | Yes  |
| Europe - EINEC / ELINCS / NLP | Yes  |
| Japan - ENCS                  | Yes  |
| Korea - KECI                  | Yes  |
| New Zealand - NZIoC           | Yes  |
| Philippines - PICCS           | Yes  |
| USA - TSCA                    | Yes  |
| Taiwan - TCSI                 | Yes  |
| Mexico - INSQ                 | Yes  |
| Vietnam - NCI                 | Yes  |
| Russia - ARIPS                | Yes  |
| <b>Legend:</b>                | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

## SECTION 16 OTHER INFORMATION

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 01/11/2019 |
|----------------------|------------|

Continued...

**Pola Luminate**

|                     |            |
|---------------------|------------|
| <b>Initial Date</b> | 13/01/2017 |
|---------------------|------------|

**SDS Version Summary**

| Version | Issue Date | Sections Updated   |
|---------|------------|--|
| 4.1.1.1 | 01/11/2019 | One-off system update. NOTE: This may or may not change the GHS classification |

**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

**Other information:**

Prepared by: SDI Limited  
3-15 Brunson Street, Bayswater Victoria, 3153, Australia  
Phone Number: +61 3 8727 7111  
Department issuing SDS: Research and Development  
Contact: Technical Director