



<u>Safety Data Sheet Cover-Sheet</u> – This page provides additional New Zealand specific information for this product, and must be read in conjunction with the Safety Data Sheet (SDS) attached.

Product Name: UltraSeal XT Hydro

Manufacturer: Ultradent

SDS Expiry: 9 October 2023

Supplier Details: Henry Schein New Zealand

23 William Pickering Drive, Albany

PO Box 101 140, North Shore, Auckland 0745

Ph. 0800 808 855

www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre – 0800POISON/0800764766 (24 Hours)

Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 6

HSNO Group Standard: Dental Products Subsidiary Hazard Group Standard 2017 HSR002558

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared on 24 January 2019

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Printing date 19.11.2018 Revision: 09.10.2018

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: <u>UltraSeal XT® Hydro™</u> · Article number: 71109, 71110, 71111 · Index number: SDS 239-001.07

· Relevant identified uses of the substance or mixture and uses advised against

Professional Dental Pit and Fissure Sealant

· Application of the substance / the mixture Professional Dental Pit and Fissure Sealant

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support @utradent.com

EC Responsible Person Ultradent Products GmbH Am Westhover Berg 30 51149 Cologne Germany Email: infoDe@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

- · Further information obtainable from: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The Regulation EC 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) shall not apply to a medical device in the finished state used in direct physical contact with the human body according to Art. 1.5 (d). Therefore, the product is exempted from the CLP labeling requirements, and no SDS is required by Regulation 1907/2006, Art. 2 (6c), REACH. Therefore, all given data, classification, and information on this SDS are provided solely on a voluntary basis.

- · Hazard pictograms GHS07
- · Signal word Warning
- · Hazard-determining components of labelling:

Triethylene Glycol Dimethacrylate

Diurethane Dimethacrylate

Organophosphine Oxide

· Hazard statements

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | | |
|-------------------------|---|-------|--|
| CAS: 109-16-0 | Triethylene Glycol Dimethacrylate | ≤20% | |
| EINECS: 203-652-6 | ♦ Skin Sens. 1, H317 | | |
| CAS: 72869-86-4 | Diurethane Dimethacrylate | <10% | |
| EINECS: 276-957-5 | ♦ Skin Sens. 1, H317 | | |
| CAS: 79-41-4 | Methacrylic Acid | <5% | |
| EINECS: 201-204-4 | Acute Tox. 3, H331; Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312 | | |
| CAS: 162881-26-7 | Organophosphine Oxide | <1% | |
| ELINCS: 423-340-5 | 💠 Skin Sens. 1, H317; Aquatic Chronic 4, H413 | | |
| CAS: 10163-15-2 | Sodium Monofluorophosphate | ≤0.2% | |
| EINECS: 233-433-0 | ♦ Acute Tox. 4, H302 | | |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · After inhalation:

Seek medical treatment in case of complaints.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 2)

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters:
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling: No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: See product labelling.
- · Specific end use(s) Professional Dental Pit and Fissure Sealant

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

79-41-4 Methacrylic Acid

WEL (Great Britain) Short-term value: 143 mg/m³, 40 ppm Long-term value: 72 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work..

(Contd. on page 4)

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 3)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

| 9 Phy | sical a | nd ch | emical | nron | ortios |
|-------|---------|-------|--------|------|--------|
| JIII | sicui u | nu cn | emicui | עטוע | ernes |

| · Information | on basic physical | and chemical | properties |
|---------------|-------------------|--------------|------------|
| | | | |

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

Odour: Acrylic

Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

· Flash point: Not applicable.

· Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

• **Density at 20 °C:** 1.67 g/cm³

• Relative density Not determined.

· Vapour density Not determined.

(Contd. on page 5)

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

| | | (Contd. of page |
|---|--|-----------------|
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| water: | Insoluble | |
| Partition coefficient: n-octanol/water: | Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| VOC (EC) | 0.00 % | |
| Solids content: | <80 % | |
| · Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| LD/LC30 | values relev | vant for classification: | |
|------------|---------------|--------------------------------------|-------|
| 109-16-0 | Triethylene | Glycol Dimethacrylate | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| | LC50 Fish | 16.4 mg/l (Fish) (Toxicity to fish) | |
| Dermal | LD50 | >2,000 mg/kg (mouse) | |
| 72869-86- | 4 Diurethan | ne Dimethacrylate | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| 79-41-4 M | lethacrylic A | Acid | |
| Oral | LD50 | 1,250 mg/kg (mouse) | |
| | | 1,060 mg/kg (rat) | |
| | | 1,200 mg/kg (rabbit) | |
| | LC50 Fish | 86 mg/l (Fish) | |
| Dermal | LD50 | 1,000 mg/kg (Guinea pig) | |
| | | 500 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | 7.1 mg/l (rat) | |
| 162881-26 | 6-7 Organop | phosphine Oxide | |
| Oral | LD50 | >2,000 mg/kg (rat) | |
| | LC50 Fish | >0.09 mg/l (Fish) (Toxicity to fish) | |
| | 1 | (Contd. o | n paş |

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

| Dermal | LD50 | >2,000 mg/kg (rat) | (Contd. of page 5)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-single exposure} \ \textit{Based on available data, the classification criteria are not met.}$
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

· Toxicity

| · Aquatic toxicity: | |
|----------------------------|--|
| 109-16-0 Triethylene Glyc | ol Dimethacrylate |
| Biodegradability | 28 days (Aerobic) (Biodegradability testing) |
| Aqua toxicity | 32 mg/l (daphnia) (No Observed Effect Concentration) |
| EC50 | >100 mg/l (Algae) (Toxicity to algae) |
| 72869-86-4 Diurethane D | imethacrylate |
| Biodegradability | 28 days (Aerobic) (Biodegradability testing) |
| EC50 | >0.6 mg/l (Algae) (Toxicity to algae) |
| | >1.2 mg/l (daphnia) (Toxicity to aquatic invertebrates) |
| 79-41-4 Methacrylic Acid | |
| EC50 | <180 mg/kg (daphnia) (Toxicity to aquatic invertebrates) |
| EC50 | 45 mg/l (Algae) (Toxicity to algae) |
| 162881-26-7 Organophos | phine Oxide |
| EC50 (static) | >1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates) |
| Aqua toxicity | ≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test) |
| Toxicity to Aquatic Plants | (static) >0.26 mg/l (Plant) (Toxicity to algae) |

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

GB2

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP 13 Sensitising

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| 14 Transport information | | |
|------------------------------|-----------------|--|
| · UN-Number | | |
| · ADR, ADN, IMDG, IATA | not regulated | |
| · UN proper shipping name | | |
| · ADR, ADN, IMDG, IATA | not regulated | |
| · Transport hazard class(es) | | |
| · ADR, ADN, IMDG, IATA | | |
| · Class | not regulated | |
| · Packing group | | |
| · ADR, IMDG, IATA | not regulated | |
| · Environmental hazards: | Not applicable. | |

Not applicable.

· Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· UN "Model Regulation": not regulated

15 Regulatory information

· Special precautions for user

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.11.2018 Revision: 09.10.2018

Trade name: UltraSeal XT® Hydro™

H413 May cause long lasting harmful effects to aquatic life.

· Contact: Customer Service

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

· Department issuing SDS: Regulatory Affairs

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4