

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name:	Trayplast
Manufacturer:	Vertex Dental
SDS Expiry:	12 July 2023
Supplier Details:	Henry Schein New Zealand 23 William Pickering Drive, Albany PO Box 101 140, North Shore, Auckland 0745 Ph. 0800 808 855 www.henryschein.co.nz
Emergency Contacts:	Poisons/Hazardous Chemical Info Centre – 0800POISON/0800764766 (24 Hours) Phone 111 for Fire, Ambulance or Police
HSNO Class/Category:	3 / 6
HSNO Group Standard:	Dental Products Flammable Group Standard 2020 HSR002556
Statements/Pictograms:	As per attached Safety Data Sheet (SDS)
Date Prepared:	This coversheet was prepared - May 2021

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.





Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 7/12/2018 Version: 1.0

I.1. Product identifier Product form			
	: Mixture		
Product name	: Vertex Trayplast		
Product group	: Trade product		
5 1	stance or mixture and uses advised against		
.2.1. Relevant identified uses	Ť		
ndustrial/Professional use spec	: Industrial For professional use only		
Jse of the substance/mixture	: Manufacture of 3D-printed applications for the dental industry		
Fitle	Use descriptors		
/ertex Trayplast	SU20		
I.3. Details of the supplier of the safety Supplier Henry Schein Hallas Ltd. Building 3, Level 6 189 – O'Riordan Street, Mascot, NSW 2020 - Australia	Manufacturer Vertex Dental Centurionbaan 190 3769 AV Soesterberg - The Netherlands T +31 886160400		
u 1300 65 88 22 customer.care@henryschein.com.au - https://he	info@vertex-dental.com - <u>www.vertex-dental.com</u> enrvschein.com.au		
I.4. Emergency telephone number			
.4. Emergency telephone number	: Australia: 13 11 26		
Emergency number	(Only for the purpose of informing medical personnel in cases of accidental intoxications. The emergency phone number is 24 hours/day available.)		

Mixtures/Substances: SDS EU 2015: According to Regulation (EU)	2015/830 (REACH Annex II)
Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Full tout of LL statements , and anotion 16	

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (CLP)

Signal word (CLP) Hazardous ingredients

Hazard statements (CLP)



- : Danger
- : methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate; ethyl methacrylate
- : H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P280 - Wear protective gloves, eye protection, face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents/container to an approved waste disposal plant.
Extra phrases	: HAZARDOUS CHEMICAL and DANGEROUS GOODS.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

5.2. Miktures			
Name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (Note D)	(CAS-No.) 80-62-6 (EC-No.) 201-297-1 (EC Index-No.) 607-035-00-6 (REACH-no) 01-2119452498-28	>= 75	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
ethyl methacrylate (Note D)	(CAS-No.) 97-63-2 (EC-No.) 202-597-5 (EC Index-No.) 607-071-00-2 (REACH-no) 01-2119490215-40	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
N,N-dimethyl-p-toluidine (Note C)	(CAS-No.) 99-97-8 (EC-No.) 202-805-4 (EC Index-No.) 612-056-00-9 (REACH-no) 01-2119937766-23	0.1 - 1	Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT RE 2, H373 Aquatic Chronic 3, H412

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note D : Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3.

However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words "non-stabilised".

Full text of H-statements: see section 16

CECTION 4. First sid massures			
SECTION 4: First aid measures			
4.1. Description of first aid measures			
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).		
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.		
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.		
4.2. Most important symptoms and effects, both acute and delayed			
Symptoms/effects after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.		
Symptoms/effects after skin contact	: Causes skin irritation.		
Symptoms/effects after eye contact	: Causes serious eye irritation.		
4.3. Indication of any immediate medical att	ention and special treatment needed		
No additional information available			

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide.

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Unsuitable extinguishing media	: Do not use water.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard	: Highly flammable liquid and vapour.	
Explosion hazard	: May form flammable/explosive vapour-air mixture.	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.	

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Evacuate unnecessary personnel.		
6.1.2. For emergency responders			
Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.		
Emergency procedures	: Ventilate area.		
6.2. Environmental precautions			
Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.			
6.3. Methods and material for containment and cleaning up			
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.		

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.		
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.		
Hygiene measures	: Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.		
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Sources of ignition. Keep in fireproof place. Keep container tightly closed.		
Incompatible products	: Strong bases. Strong acids.		
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.		
7.3. Specific end use(s)			

No additional information available

SECTION 8: Exposure controls/personal protection 8.1. Control parameters			
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)			
Australia	Local name		Methyl methacrylate
Australia	TWA (mg/m ³)		208 mg/m ³
Australia	TWA (ppm)		50 ppm
Australia	STEL (mg/m ³)		416 mg/m ³
Australia	STEL (ppm)		100 ppm
Australia	Remark (AU)		Sen - Respiratory and/or Skin Sensitiser.
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)			
DNEL/DMEL (Workers)			
Acute - local effects, dermal	ute - local effects, dermal 1.5 mg/cm ²		

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)			
Long-term - systemic effects, dermal	13.67 mg/kg bodyweight/day		
Long-term - local effects, dermal	1.5 mg/cm ²		
Long-term - systemic effects, inhalation	208 mg/m ³		
Long-term - local effects, inhalation	208 mg/m³		
DNEL/DMEL (General population)			
Acute - local effects, dermal	1.5 mg/cm ²		
Long-term - systemic effects, inhalation	74.3 mg/m³		
Long-term - systemic effects, dermal	8.2 mg/kg bodyweight/day		
Long-term - local effects, dermal	1.5 mg/cm ²		
Long-term - local effects, inhalation	104 mg/m³		
PNEC (Water)			
PNEC aqua (freshwater)	0.94 mg/l		
PNEC aqua (marine water)	0.94 mg/l		
PNEC aqua (intermittent, marine water)	0.94 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	5.74 mg/kg bw		
PNEC (Soil)			
PNEC soil	1.47 mg/kg bw		
PNEC (STP)			
PNEC sewage treatment plant	10 mg/l		
N,N-dimethyl-p-toluidine (99-97-8)			
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.694167 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	1.224 mg/m ³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.173542 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	0.301812 mg/m ³		
Long-term - systemic effects, dermal	0.292522 mg/kg bodyweight/day		
PNEC (Water)			
PNEC aqua (freshwater)	0.0137 - 0.15259 mg/l		
PNEC aqua (marine water)	0.00137 - 0.015259 mg/l		
PNEC aqua (intermittent, freshwater)	0.0137 - 0.15259 mg/l		
PNEC (Sediment)			
PNEC sediment (freshwater)	45.378 - 48.245 mg/kg bw		
PNEC sediment (marine water)	45.378 - 48.245 mg/kg bw		
PNEC (Soil)			
PNEC soil	18.677 - 20.365 mg/kg bw		
PNEC (STP)			
PNEC sewage treatment plant	1.36 - 4.286 mg/l		
ethyl methacrylate (97-63-2)			
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	10.8 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	370.5 mg/m ³		
Long-term - local effects, inhalation	267 mg/m³		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethyl methacrylate (97-63-2)	nethacrylate (97-63-2)	
DNEL/DMEL (General population)	MEL (General population)	
Long-term - systemic effects, inhalation	76 mg/m³	
Long-term - systemic effects, dermal	6.5 mg/kg bodyweight/day	
Long-term - local effects, inhalation	189.8 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	1.8 mg/l	
PNEC aqua (marine water)	1.8 mg/l	
PNEC aqua (intermittent, freshwater)	1.8 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	40 mg/kg bw	
PNEC (Soil)		
PNEC soil	1.47 mg/kg bw	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
8.2. Exposure controls		

Appropriate engineering controls:

Ensure that there is a suitable ventilation system.

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration. The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN 374. penetration time (maximum wearing period): 60 m. Suitable material: butyl rubber. Layer thickness : 0,7 mm

Eye protection:

Wear eye glasses with side protection according to EN 166.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. At high concentrations: Wear respiratory protection. Combination filtering device (DIN EN 141). High gas/vapour concentration: gas mask with filter type A

Personal protective equipment symbol(s):



Environmental exposure controls:

Use appropriate container to avoid environmental contamination.

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes.

Freezing point	: No data available	
Melting point	: -48 °C	
Relative evaporation rate (butylacetate=1)	: No data available	
рН	: Not applicable	
Odour threshold	: No data available	
Odour	: Ester. characteristic. strong. Acrid.	
Colour	: clear. Colourless.	
Physical state	: Liquid	
9.1. Information on basic physical and chemical properties		
SECTION 9: Physical and chemical		

Boiling point	: 100.5 °C
Flash point	: 10 °C
Auto-ignition temperature	: 421 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour
Vapour pressure	: 3.6 Pa @ 20°C
Relative vapour density at 20 °C	: No data available
Relative density	: 0.94 @ 15.5 °C
Solubility	: miscible with most organic solvents.
	Water: 1.6 % slightly soluble
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Explosive limits	: 2.1 - 12.5 vol %
9.2. Other information	
VOC content	: 100 %

SECTION 10: Stability and reactivity
10.1. Reactivity
No additional information available
10.2. Chemical stability
Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
10.3. Possibility of hazardous reactions
Not established.
10.4. Conditions to avoid
Direct sunlight. Extremely high or low temperatures. Open flame.
10.5. Incompatible materials
Strong acids. Strong bases.
10.6. Hazardous decomposition products
fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information		
11.1. Information on toxicologica	effects	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		

entry methaci yiate, methy z-methyprop-z-enoate, methyr z-methypropenoate (00-02-0)	
LD50 oral rat	7900 - 9400 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (mg/l)	29.8 mg/l/4h

N,N-dimethyl-p-toluidine (99-97-8)	
LD50 oral rat	1650 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	1.4 mg/l/4h

ethyl methacrylate (97-63-2)		
LD50 oral rat	13424 mg/kg	
LC50 inhalation rat (mg/l)	55 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
	pH: Not applicable	
Serious eye damage/irritation	: Causes serious eye irritation.	
	pH: Not applicable	
Respiratory or skin sensitisation	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	

Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)	
LOAEC (inhalation, rat, vapour, 90 days)	416 mg/m³ air
NOAEL (oral, rat, 90 days)	124.1 - 164 mg/kg bodyweight/day
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	500 - 1000 ppm

N,N-dimethyl-p-toluidine (99-97-8)	
LOAEL (oral, rat, 90 days)	201.786 mg/kg bodyweight/day

ethyl methacrylate (97-63-2)	nethacrylate (97-63-2)	
NOAEL (oral, rat, 90 days)	30 - 300 mg/kg bodyweight/day	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	310 ppm	
Aspiration hazard	: Not classified	
Additional information	: Based on available data, the classification criteria are not met	
Potential adverse human health effects and	: Based on available data, the classification criteria are not met.	

Potential adverse human health effects and
symptoms

SECTION 12: Ecological information				
12.1. Toxicity				
Ecology - general	: Avoid release to the environment.			
Acute aquatic toxicity	Not classified			
Chronic aquatic toxicity	Not classified			
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)				
LC50 fishes	79 mg/l			
EC50 Daphnia	69 mg/l			
EC50 72h algae (1)	110 mg/l			
LOEC (chronic)	68 mg/l (21 d)			
NOEC (acute)	40 mg/l (4 d)			
NOEC chronic fish	37 mg/l (21 d)			

N,N-dimethyl-p-toluidine (99-97-8)		
LC50 fishes	45 - 52.8 mg/l	
EC50 Daphnia	13.7 mg/l	
EC50 other aquatic organisms 1	42.864 mg/l microorganisms	
EC50 72h algae (1)	22 - 24.37 mg/l	

ethyl methacrylate (97-63-2)		
LC50 fishes	100 mg/l	
EC50 Daphnia	66 mg/l	
EC50 72h algae (1)	72 - 110 mg/l	
NOEC (acute)	41 mg/l (48 h)	
NOEC chronic fish	9.4 mg/l (35 d)	

NOEC chronic crustacea	18 mg/l (21 d)	
12.2. Persistence and degradability		
Vertex Trayplast		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
Vertex Trayplast		
Bioaccumulative potential	Not established.	

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)		
Log Pow	1.38 @ 20 °C and pH 7	

N,N-dimethyl-p-toluidine (99-97-8)		
Log Pow	1.729 @ 35 °C and pH 5.6	

ethyl methacrylate (97-63-2)		
Log Pow	1.87 @ 20 °C and pH 7	
12.4. Mobility in soil		
No additional information available		
12.5. Results of PBT and vPvB assessment		
No additional information available		
12.6. Other adverse effects		
Additional information	: Avoid release to the environment.	

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional legislation (waste)	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Can be dumped in according to local regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADN / AD				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number				
1247	1247	1247	1247	1247
14.2. UN proper shippin	g name			
METHYL METHACRYLATE MONOMER, STABILIZED	METHYL METHACRYLATE MONOMER, STABILIZED	Methyl methacrylate monomer, stabilized	METHYL METHACRYLATE MONOMER, STABILIZED	METHYL METHACRYLATE MONOMER, STABILIZED
Transport document descr	iption			·
UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED (methyl methacrylate; methyl 2-methylprop-2- enoate; methyl 2- methylpropenoate; acetone; propan-2-one; propanone), 3, II, (D/E)	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II (8°C c.c.)	UN 1247 Methyl methacrylate monomer, stabilized, 3, II	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED, 3, II	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED 3, II
14.3. Transport hazard o	class(es)			
3	3	3	3	3
3				3
7/12/2018 (Version: 1.0)		AU - en		8/

14.4. Packing group						
II	II	I	II	II		
14.5. Environmental haza	ards	•	•			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No		
No supplementary informatior	n available					
14.6. Special precautions	s for user					
Overland transport						
Classification code (ADR)	: F					
Special provisions (ADR)	: 3					
Limited quantities (ADR)	: 1					
Excepted quantities (ADR)	: E					
Packing instructions (ADR)		001, IBC02, R001				
Mixed packing provisions (AD	,	IP19				
Portable tank and bulk contain (ADR)						
Portable tank and bulk contain (ADR)						
Tank code (ADR)		GBF				
Vehicle for tank carriage	: F					
Transport category (ADR) Special provisions for carriage	: 2					
Special provisions for carriage	• • •	° 2, S4, S20				
Hazard identification number						
Orange plates	(Iternier 140.)					
		339 1247				
Tunnel restriction code (ADR)	: D	/E				
Transport by sea						
Special provisions (IMDG)	: 3	86				
Limited quantities (IMDG)	: 1	L				
Excepted quantities (IMDG)	: E	2				
Packing instructions (IMDG)		: P001				
IBC packing instructions (IMD	G) : IE	3C02				
Tank instructions (IMDG)		: T4				
Tank special provisions (IMD)	•	: TP1				
EmS-No. (Fire)		: F-E				
EmS-No. (Spillage)		: S-D				
Stowage category (IMDG)		: C				
Stowage and handling (IMDG		W1, SW2				
Flash point (IMDG) Properties and observations (: 8°C c.c. : Colourless, volatile liquid. Flashpoint: 8°C c.c. Explosive limits: 1.5% to 11.6% Immiscible				
		ith water. Irritating to skin, eye		5. 1.3 % to 11.0 % inimiscio		
Air transport	-	0				
PCA Excepted quantities (IAT						
PCA Limited quantities (IATA)		341				
PCA limited quantity max net PCA packing instructions (IAT						
PCA packing instructions (IAT PCA max net quantity (IATA)	A) . 5 : 5					
CAO packing instructions (IATA)						
CAO max net quantity (IATA)	: 6) : 6)					
Special provisions (IATA)		209				
ERG code (IATA)	: 3					
\ <i>/</i>						
Inland waterway transport						

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1307/2000 (REACH) with	its amenument regulation (
Special provisions (ADN)	: 386
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1
Rail transport	
Classification code (RID)	: F1
Special provisions (RID)	: 386
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 339

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the R	EACH Regulation (EC) No 1907/2006:
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2- methylpropenoate - ethyl methacrylate - N,N-dimethyl-p-toluidine
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Vertex Trayplast - methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - ethyl methacrylate
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Vertex Trayplast - methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - ethyl methacrylate - N,N-dimethyl-p- toluidine
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	N,N-dimethyl-p-toluidine
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2- methylpropenoate - ethyl methacrylate

Contains no REACH Annex XIV substances

VOC content
Directive 2012/18/EU (SEVESO III)

: 100 %

15.1.2. National regulations No additional information available 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

applicable.

SECTION 16: Other information

Abbreviations and acronym	s:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DNEL	Derived-No Effect Level	
EC50	Median effective concentration	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
STP	Sewage treatment plant	
vPvB	Very Persistent and Very Bioaccumulative	
Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.	
Other information	: DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond ou control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be	

Full text of H- and EUH-statements:			
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3		
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1	Skin sensitisation, Category 1		
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2		
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation		
H225	Highly flammable liquid and vapour		
H301	Toxic if swallowed.		
H311	Toxic in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H335	May cause respiratory irritation.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H412	Harmful to aquatic life with long lasting effects.		

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of use descriptors				
SU20	Health services			
Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Flam. Liq. 2	H225	On basis of test data		
Skin Irrit. 2	H315	Calculation method		
Eye Irrit. 2	H319	Calculation method		
Skin Sens. 1	H317	Calculation method		
STOT SE 3	H335	Calculation method		

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product